



BIOLUBE INC.

PO Box 9732 Fort Wayne, IN 46899

www.biolube1.com sales@biolube1.com

260-414-9633 Fax 260-440-3163

Biolube 2

A synthetic oil blend that will not get gummy or burn on the blade. Biolube 2 is designed to lubricate, cool, and retard resin and pitch build-up on band saw blades, circular saw blades, and other wood tooling. Biolube 2 provides over twice the lubricating strength of diesel fuel. Many mills use #2 to lubricate the headrig ways and carriage wheels and rails. Biolube 2 is low cost, odorless, non-irritating to skin, nontoxic and environmentally friendly. #2 does not contain silicones and will not stain or discolor wood.

Biolube 2 replaces diesel fuel in spray, drip, and wick systems. Mills using about 2 quarts per shift of #2 find the cost lower than diesel fuel while eliminating the fire hazard, personal safety, and odor problems of diesel.

Biolube 2 is most effectively applied through Biolube spray systems which give the ultimate in application and volume adjustment. Wick, drip, and other spray systems run #2 effectively.

Biolube #2 is nontoxic, biodegradable, non-irritating, and has FDA approval. It does not contain any chemicals listed in SARA Title III, Section 313, or in OSHA 29 CFR 1910.

PHYSICAL DATA

Raw Material Base	Ester Oil	Color	Clear / Light
Boiling Point	N/A	Specific Gravity	0.837
Flash Point	>143°C, >290°F	Freeze Point	N/A
Percent Volatiles by Weight	N/A	Lubricity Rating	0.039 (diesel fuel=0.074)
Solubility	100%	Odor	None
USED ON:		Pour Point	-46°C, -50°F

Gang Rip Saws by: Mereen-Johnson, SCMI, Cornell, Diehl, Brewer and Yates.

Band Saws by: McDonough, Salem, Filer & Stowell, Wheiland, Brewer, Kimwood, Ferrari, Forestor.

UNIT (Gallons) CATALOG #

DRUM (55 Gallons) BL 2-55