



BIOLUBE INC.

PO Box 9732 Fort Wayne, IN 46899

www.biolube1.com sales@biolube1.com

260-414-9633 Fax 260-440-3163

Lubie® 210 SPF saw lube

A new and unique synthetic oil blend formulated specifically to prevent softwood (SPF) pitch build up; it will not get gummy or burn on the blade. Lubie® 210 is designed to lubricate, cool, and retard resin and pitch build-up on band saw blades, circular saw blades, and other wood tooling. Additionally it provides over twice the lubricating strength of diesel fuel. Many mills use #210 to lubricate the headrig ways and carriage wheels and rails. Lubie® 210 is low cost, odorless, non-irritating to skin, nontoxic, environmentally friendly and does not contain silicones and will not stain or discolor wood.

Lubie® 210 replaces diesel fuel in spray, drip, and wick systems. Mills using about 2 quarts per shift of 210 find the cost lower than diesel fuel while eliminating the fire hazard, personal safety, and odor problems of diesel.

Lubie® 210 is most effectively applied through Biolube's Lubie® spray systems which give the ultimate in application and volume adjustment. Wick, drip, and other spray systems run #210 effectively.

Lubie® #210 is nontoxic, biodegradable and non-irritating. It does not contain any chemicals listed in SARA Title III, Section 313, or in OSHA 29 CFR 1910.

PHYSICAL DATA

Raw Material Base	Ester Oil	Color	Clear / Light
Boiling Point	N/A	Specific Gravity	0.837
Flash Point	>143°C, >290°F	Freeze Point	N/A
Percent Volatiles by Weight	N/A	Lubricity Rating	0.039 (diesel fuel=0.074)
Solubility	100%	Odor	None
Pour Point	-46°C, -50°F		

USED ON:

Gang Rip Saws by: Mereen-Johnson, SCMI, Cornell, Diehl, Brewer and Yates.

Band Saws by: McDonough, Salem, Filer & Stowell, Wheiland, Brewer, Kimwood Ferrari, Forestor.

UNIT (Gallons) CATALOG #

DRUM (55 Gallons) BL 210-55

Copyright © 2014 Biolube Inc. All rights reserved. The Lubie Logo, Lubie™, and all products denoted with ® or ™ are trademarks or registered trademarks of Biolube Inc.

