



## **BIOLUBE INC.**

**PO Box 9732 Fort Wayne, IN 46899**

**[www.biolube1.com](http://www.biolube1.com) [sales@biolube1.com](mailto:sales@biolube1.com)**

**260-414-9633 Fax 260-440-3163**

### **Lubie® GPX Bed Lube**

For cedar GPX is a new unique blended formulation of synthetic lubricants in a fast evaporating solvent carrier. Lubie® GPX is formulated to reduce friction, decrease heat and prevent wood resin build up on moulder beds, planer beds and other wood transfer equipment.

Lubie® GPX dries very quickly, leaving a durable lubricating film on the bed. Wood staining, painting, laminating and other finishing operations generally are not affected because there is no silicone, grease or wax used in the formulation.

Lubie® GPX is designed for use in automatic, semi-automatic and manual bed injector systems. The very low viscosity allows it to also be used in spray bottles.

#### **PHYSICAL DATA**

Raw Material Base	Petroleum Hydrocarbon	Color	Light Yellow
Boiling Point	300°F	Specific Gravity	0.813
Flash Point	135°F (COC)	Freeze Point	N/A
Percent Volatiles by Weight	90%	Lubricity Rating	0.035 (diesel fuel=0.074)
Solubility	None	Odor	Light Petroleum

#### **USED ON:**

Moulders by: Weinig, Wadkins, Yates, Madison, Tri State and Diehl.

Package Saws: Holtec, L&M.

UNIT (Gallons)	CATALOG #
CASE (4 Gallons)	BL GPX-1
PAIL (5 Gallons)	BL GPX-5
DRUM (55 Gallons)	BL GPX-55